



**UT330 SERIES**  
**USB Datalogger**  
 UT330A / UT330B / UT330C

**NEW**



**UT330A**



**UT330B**



**UT330C**

**SPECIFICATIONS**

USB

Specifications	Range	UT330A	UT330B	UT330C
<b>Model</b>				
Temperature(°C)	Range	-40°C~80°C(-40°F~176°F)	✓	✓
	Accuracy	0°C~40°C	±0.5°C	±0.5°C
		-30°C~0°C,40°C~70°C	±1°C	±1°C
		-40°C~-30°C,70°C~80°C	±2°C	±2°C
Resolution	0.1°C/0.1°F	✓	✓	
Relative Humidity	Range	0%RH~100%RH		✓
	Accuracy	20%RH~80%RH		±3%RH
		<20%RH or >80%RH		±5%RH
Resolution	0.1%RH		✓	
Atmospheric Pressure	Range	750hPa~1100hPa		✓
	Accuracy			±3 hPa
	Resolution	0.1hPa		✓
IP67		✓	✓	✓
°C/°F Selection		✓	✓	✓
Temperature Offset Settings		✓	✓	✓
Humidity Offset Settings			✓	✓
Pressure Offset Settings				✓
Data Logging		60000	60000	60000
Data Recall		✓	✓	✓
USB Interface		✓	✓	✓
Auto Record Time Setup		✓	✓	✓
User Name Settings		✓	✓	✓
Alarm Threshold		✓	✓	✓
Start Mode Setup		✓	✓	✓

**GENERAL CHARACTERISTICS**

Power	3.6V 1/2 AA Lithium Battery(ER14250) x 1
Product Color	Grey
Product Net Weight	52g
Product Size	122mmx30mmx24mm
Standard Accessories	Batteries, PC Software CD, Bracket, Screws
Standard Individual Packing	English Manual Batteries
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	575mm x 395mm x 250mm(0.056CBM Per Standard Carton)
Standard Carton Gross Weight	10.5Kg
<b>Optional Accessories</b>	Magnet Bracket (UT-B22)