



EN:61326-1
EN:60825-1

NEW



■ UT393A



■ UT393B

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT393A	UT393B
Model		UT393A	UT393B
Distance Measurement	0.1m~100m 4in~328ft	±1.5mm ±0.06in	±1.5mm ±0.06in
Measuring Units	m/in/ft.		
Angle Measurement	-45°~+45°	±0.3°	±0.3°
Level Measurement	-45°~+45°	±0.3°	±0.3°
Laser Class	Class 2 (II)		
Laser Power	<1mW		
Laser Wavelength	630nm~670nm		
Features			
Area/Volume Calculation		✓	✓
Indirect Measurement	Pythagorean	✓	✓
Single/Continuous Measurement		✓	✓
Auto Horizontal Measurement		✓	✓
Auto Vertical Measurement		✓	✓
Triangle Measurement		✓	✓
Addition/Subtraction		✓	✓
MAX/MIN		✓	✓
Reference Level Setting		✓	✓
Level Bubble		✓	✓
Thermometer		✓	✓
Auxiliary Measurement	Timer, Comparison and Edit Measurement	✓	✓
Parameter Settings	Date/Time, Constant, Brightness, Buzzers	✓	✓
USB Data Interface			✓
Data Storage		30	1000
Language Selection	Chinese/English	✓	✓
Error Indication		✓	✓
Factory Settings		✓	✓
Auto Power Off	Around 3 Minutes	✓	✓
Battery Life	>15000 Measurements	✓	✓
Battery Level Indication	Instant Capacity Prompt	✓	✓
Dust and Water Proof Rating	IP54	✓	✓

GENERAL CHARACTERISTICS

Power	Li-ion Battery(1200mAh)
LCD	2" Color Display
Product Color	Red and Grey
Product Net Weight	110 g
Product Size	50mm × 29mm × 125mm
Standard Accessories	Battery, Charger, Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	590mm × 365mm × 370mm
Standard Carton Gross Weight	17.5 Kg