

**UT601****Modern Inductance Capacitance Meters**

CE

**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
Resistance	20W/200W/2kV/20kV/200kV/2MW/20MW/200MW/2000MW	±(0.8%+1)
Capacitance	200pF/2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(0.5%+10)
Special Functions		
Diode		✓
Continuity Buzzer		✓
Transistor		✓
Low Battery Display		✓
Max. Display	1999	✓

**GENERAL CHARACTERISTICS**

Power	9V Battery (6F22)
LCD Size	61 x 32 mm
Product Colour	Grey Holster-Red
Product Net Weight	310g
Product Size	172 x 83 x 38mm
Standard Accessories	Test Clip, Battery, English Manual, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085CBM Per Standard Carton)
Standard Carton Gross Weight	21kg

**UT603****Modern Inductance Capacitance Meters**

CE

**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
Resistance	200W/2kW/20kV/200kV/2MW/20MW	±(0.8%+1)
Capacitance	2nF/20nF/200nF/2mF/20mF/200mF/600mF	±(1%+5)
Inductance	2mH/20mH/200mH/2H/20H	±(2%+8)
Special Functions		
Diode		✓
Continuity Buzzer		✓
Transistor		✓
Low Battery Display		✓
Max. Display	1999	

**GENERAL CHARACTERISTICS**

Power	9V Battery (6F22)
LCD Size	61 x 32 mm
Product Colour	Grey Holster-Red
Product Net Weight	312g
Product Size	172 x 83 x 38mm
Standard Accessories	Test Clip, Battery, English Manual, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085CBM Per Standard Carton)
Standard Carton Gross Weight	21kg