

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## RS232 to USB Adapter Cable with COM Retention (USB-A to DB9 M/M), FTDI, 5 ft.

## MODEL NUMBER: U209-005-COM







RS232 to USB adapter cable with DB9 serial connector lets you connect RS232 devices to your computer's USB port.

### Features

#### Connects a Barcode Scanner or Other DTE Serial Device to Your Computer's USB-A Port

This five-foot serial RS232 to USB adapter cable turns your computer's USB port into an RS232 serial port and avoids the expense of upgrading your reliable serial devices. No external power source is needed. Just connect the cable to your computer and insert the included CD into your computer's CD drive in order to launch the driver and assign the cable a COM port. It supports USB 2.0 specifications and data transfer speeds up to 230 Kbps, which is almost twice as fast as a built-in serial port. It is backward compatible with USB 1.1 devices.

#### COM Retention Feature for Convenient Reassigning of COM Values to Ports

The hot-swappable RS232-port-to-USB adapter with built-in FTDI chipset offers COM retention. It automatically reassigns the same COM port values to each port, so when the cable is disconnected or the system is rebooted, no additional configuration is needed. The cable also supports remote wake-up and power management.

#### Double Shielding Protects Your Data from Destructive Line Noise

Foil and braid shielding helps fight against electromagnetic interference and radio frequency interference (EMI/RFI) that impedes your signal and can distort or destroy data. The auto-sensing feature solves DCE/DTE conflicts without the need for cross-wired serial cables or adapters.

#### 3-Year Warranty

The U209-005-COM is backed by a 3-year warranty, ensuring reliability and performance.

## Highlights

- Supports data transfer speeds up to 230 Kbps—double the speed of a built-in serial port
- Automatically reassigns COM values to each port to avoid additional configuration
- USB-powered, so no bulky or obtrusive external power supply is required
- Double shielding protects against EMI/RFI line noise that can distort or destroy data
- Compatible with Windows, Mac and Linux—works with most computers

#### Applications

- Connect and control serialbased point-of-sale printers, barcode readers, surveillance cameras and card readers
- Create messages for LED sign boards with serial ports to avoid the expense of upgrading your sign board

#### System Requirements

- Windows, Mac or Linux
- Computer with an available USB port

#### Package Includes

- U209-005-COM RS232 to USB Adapter Cable, 5 ft.
- Driver CD
- Owner's manual

# **Specifications**



037332210227		
Serial (RS232); USB (all versions)		
5		
60		
Yes		
152		
PHYSICAL		
Box		
0.15		
0.07		
PCB & PVC		
Black		
VW-1		
32 to 140 F (0 to 60 C)		
-4 to 176 F ( -20 to 80 C)		
0% to 80% RH, Non-Condensing		
CONNECTIONS		
0		
USB A (MALE)		
DB9 (MALE)		
Nickel		
Gold		
FEATURES & SPECIFICATIONS		
USB 2.0 (up to 480 Mbps)		
Yes		
Yes		
Tested to CE, FCC, RoHS, REACH, WEEE		



WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies